



CLASSIC aluminium mat with rubber, height 20-22 mm

Technical data

Description

Flat aluminium profiles with rubber. Roll-up, easy to clean. Stops very large amounts of dirt in spaces between profiles. Active rubber profile notched perpendicular and parallel to the length, safe under the conditions of freezing drizzle.

Application

Recommended for indoor and outdoor areas. Suitable for entrances with intensive pedestrian traffic (up to 2000 people daily) - shopping malls, airports, stations, offices, hotels, banks, entrances to multi-family and commercial buildings, etc. In order to maintain high performance characteristics, it is recommended to use it with other elements (such as: linear brush, scraping strip).

Materials

Support profiles: aluminium / height 17mm x width 24mm / Standard EN-573-3
Insert: cross-ribbed rubber Standard BN-80 / 6613-04
Connector of elements: stainless steel line Ø 3mm, every 30 cm, the minimum tensile strength of 5.06 kN / Standard EN 12385-4
Connecting element: chrome-plated brass cylinder with clamping screw / DIN EN ISO 9001: 2000
Spacers: rubber of 5mm or 3mm thickness / Standard BN-80 / 6613-04
Backing: acoustic foam for indoor / ISO 9001: 2008

Dimensions

Height: 20 mm – without backing
22 mm – with backing
Weight: 17.5 kg/m²

Colours

Support profile: natural aluminium
Rubber: black

Adhesive

natural rubber solution / Standard PN-EN-1239-211-U

Permissible load

1500 kg/1 dm²

Attestation

PZH no. HK/B/1001/01/2017 (National Institute of Public Health, Warsaw, Poland). In combination with brush 3:1 gives the slip resistance in accordance with standard DIN51130 - R10.