



SPECIAL aluminium mat with rubber, height 27 mm

Technical data

Description

Aluminium profiles for mats of various irregular shapes combined with a vinyl connector or steel cable that allows the formation of various planes with any curves. The aluminium profiles are completed with natural rubber, double-grooved. Roll-up, easy to clean. Stops dirt from through 24-mm-deep spaces between the profiles. Safe under the conditions of freezing drizzle. Stops dirt and water in increased amounts due to raised surface of rubber.

Application

Mats of this type are ideal for round doors and other complex surfaces. Recommended for outdoor areas and indoor vestibules. Suitable for zones with intensive pedestrian traffic (over 2000 people a day). Mat with acoustic backing as a standard.

Materials

Support profiles: aluminium / height 20mm x width 30mm / Standard EN-573-3

Insert: cross-ribbed rubber/ Standard BN-80/6613-04

Connector of elements: PVC connector/PN-EN 607; PN-EN 12200/ stainless steel cable \varnothing 3mm, every 30 cm, the minimum tensile strength of 5.06 kN / Standard EN12385-4

Backing: rubber strips/ Standard BN-80/6613-04

Dimensions

Height: 27 mm
Weight: 17kg/m²

Colour:

Support profile: natural aluminium

Rubber: black, grey (possibility of use)

Adhesive

natural rubber solution / Standard PN-EN-1239-211-U

Permissible load

600 kg/1dm²

Attestation

PZH no. HK/B/1001/01/2017 (National Institute of Public Health, Warsaw, Poland)